



LT Light Truck
Camioneta
Comerciais
Camionnette

CRUGEN HT51

Highway Terrain



English

- Long tread life with all season capabilities
- Excellent safety on the road covered with snow
- With 3D Sipe application, handling performance and snow traction performance have been improved
- M+S and 3PMSF (3 Peak-Mountain-Snowflake) certified



Español

- Capacidad con una larga vida de la banda de rodadura para todas las estaciones
- Excelente seguridad para camino cubierto de nieve
- Ranuras tridimensionales que mejoran el manejo y la tracción en la nieve
- Marcaje M+S y 3PMSF (3 Picos de Montaña y Copo de Nieve)



Português

- Longa vida do piso com todas as capacidades da época
- Excelente segurança na estrada coberta de neve
- Com a aplicação de ranhuras 3D, a dirigibilidade e o desempenho de tração em neve e lama foram melhorados
- Com marcação M+S e símbolo 3PMSF (3 floco de neve em topo de montanha)



Français

- Pneu toutes saisons avec une longévité de la bande de roulement prolongée
- Une excellente sécurité sur route enneigée
- Grâce à la lamellisation 3D, la tenue de route et la traction sur neige sont améliorées
- Marquage M+S et 3PMSF (3 Pics de Montagnes Symbole Flocon de neige)



Highway Terrain

All Season

Handling

3PMSF



Award & Test Results



Consumer Reports (2021.06)
: Ranking 5

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth		Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector
				bar	psi	kg	lbs	mm	inch	mm	inch	mm	x/32"				
Black Sidewall																	
22"	285/45 R22 XL	114H	9.5	9.0 - 10.5	3.4	50	1180 2601	285	11.2	815 32.1	9.8 12.3	379	2486	720	A A	○	
20"	P275/55 R20	111T	8.5	7.5 - 9.5	3.5	51	1090 2403	284	11.2	810 31.9	9.8 12.3	372	2471	720	A A	-	
	P275/60 R20	114T	8.0	7.5 - 9.5	3.5	51	1180 2601	279	11.0	838 33.0	9.8 12.3	383	2556	720	A A	-	
	265/50 R20 XL	111T	8.5	7.5 - 9.5	3.4	50	1090 2403	277	10.9	774 30.5	9.8 12.3	358	2361	720	A A	-	
19"	245/55 R19	103T	7.5	7.0 - 8.5	3.5	51	875 1929	253	10.0	753 29.6	9.8 12.3	347	2297	720	A A	-	
18"	LT 275/65 R18 10 S	123R	8.0	7.5 - 9.0	5.5	80	1550 3415	279	11.0	815 32.1	11.2 14.1	368	2486	-	-	-	
	D 120						1400 3085										
	P275/65 R18	114T	8.0	7.5 - 9.5	3.5	51	1180 2601	279	11.0	815 32.1	9.8 12.3	368	2486	720	A A	-	
	LT 275/70 R18 10 S	125R	8.0	7.0 - 9.0	5.5	80	1650 3640	279	11.0	843 33.2	11.2 14.1	379	2571	-	-	-	
	D 122						1500 3305										
	265/60 R18	110T	8.0	7.5 - 9.5	3.5	51	1060 2337	272	10.7	775 30.5	9.8 12.3	353	2364	720	A A	-	
	P265/65 R18	112T	8.0	7.5 - 9.5	3.5	51	1120 2469	272	10.7	801 31.5	9.8 12.3	363	2443	720	A A	-	
	P265/70 R18	114T	8.0	7.0 - 9.0	3.5	51	1180 2601	272	10.7	829 32.6	9.8 12.3	374	2528	720	A A	-	
	LT 265/70 R18 10 S	124R	8.0	7.0 - 9.0	5.5	80	1600 3525	272	10.7	829 32.6	11.2 14.1	374	2528	-	-	-	
	D 121						1450 3195										
17"	255/60 R18 XL	112H	7.5	7.0 - 9.0	3.4	50	112 2469	260	10.2	763 30.0	9.8 12.3	348	2327	720	A A	-	
	P255/70 R18	112T	7.5	6.5 - 8.5	3.5	51	1120 2469	260	10.2	815 32.1	9.8 12.3	368	2486	720	A A	-	
	245/60 R18	105T	7.0	7.0 - 8.5	3.5	51	925 2039	248	9.8	751 29.6	9.8 12.3	343	2291	720	A A	-	
	235/60 R18	103H	7.0	6.5 - 8.5	3.5	51	875 1929	240	9.4	739 29.1	9.8 12.3	339	2254	720	A A	-	
	265/65 R17	112T	8.0	7.5 - 9.5	3.5	51	1120 2469	272	10.7	776 30.6	9.8 12.3	350	2367	720	A A	-	
	P265/70 R17	113T	8.0	7.0 - 9.0	3.5	51	1150 2535	272	10.7	804 31.7	9.8 12.3	361	2452	720	A A	-	
	LT 265/70 R17 10 S	121S	8.0	7.0 - 8.5	5.5	80	1450 3195	272	10.7	804 31.7	11.2 14.1	361	2452	-	-	-	
	D 118						1320 2910										
	255/65 R17	110T	7.5	7.0 - 9.0	3.5	51	1060 2337	260	10.2	764 30.1	9.8 12.3	345	2330	720	A A	-	
	255/70 R17	112T	7.5	6.5 - 8.5	3.5	51	1120 2469	260	10.2	790 31.1	9.8 12.3	356	2410	720	A A	-	
16"	245/65 R17 XL	111T	7.0	7.0 - 8.5	3.4	50	1090 2403	248	9.8	750 29.5	9.8 12.3	340	2288	720	A A	-	
	245/70 R17	110T	7.0	6.5 - 8.0	3.5	51	1060 2337	248	9.8	776 30.6	9.8 12.3	350	2367	720	A A	-	
	LT 245/70 R17 10 S	119S	7.0	6.5 - 8.0	5.5	80	1360 3000	248	9.8	776 30.6	11.2 14.1	350	2367	-	-	-	
	D 116						1250 2755										
	LT 245/75 R17 10 S	121S	7.0	6.5 - 7.5	5.5	80	1450 3195	248	9.8	800 31.5	11.2 14.1	359	2440	-	-	-	
	D 118						1320 2910										
	235/60 R17	102T	7.0	6.5 - 8.5	3.5	51	850 1874	240	9.4	714 28.1	9.8 12.3	326	2178	720	A A	-	
	235/65 R17	104T	7.0	6.5 - 8.5	3.5	51	900 1984	240	9.4	738 29.1	9.8 12.3	335	2251	720	A A	-	
	P235/70 R17 XL	108T	7.0	6.0 - 8.0	3.4	50	990 2183	240	9.4	762 30.0	9.8 12.3	345	2324	720	A A	-	
	235/75 R17	109T	6.5	6.0 - 8.0	3.5	51	1030 2271	235	9.3	784 30.9	9.8 12.3	353	2391	720	A A	-	
LT 235/80 R17 10 S	120R	6.5	6.0 - 7.5	5.5	80	1400 3085	235	9.3	808 31.8	11.2 14.1	363	2464	-	-	-		
D 117						1285 2835											
225/65 R17	102T	6.5	6.0 - 8.0	3.5	51	850 1874	228	9.0	724 28.5	9.8 12.3	330	2208	720	A A	-		
16"	P275/70 R16	114T	8.0	7.0 - 9.0	3.5	51	1180 2601	279	11.0	792 31.2	9.8 12.3	354	2416	720	A A	-	
	265/70 R16	112T	8.0	7.0 - 9.0	3.5	51	1120 2469	272	10.7	778 30.6	9.8 12.3	348	2373	720	A A	-	
	LT 265/70 R16 08 S	117Q	8.0	7.0 - 8.5	4.5	65	1285 2835	272	10.7	778 30.6	11.2 14.1	348	2373	-	-	-	
	D 114						1180 2600										
	P265/75 R16	114T	7.5	7.0 - 9.0	3.5	51	1180 2601	267	10.5	804 31.7	9.8 12.3	358	2452	720	A A	-	
255/70 R16	111T	7.5	7.0 - 9.0	3.5	51	1090 2403	260	10.2	764 30.1	9.8 12.3	343	2330	720	A A	-		
245/70 R16 XL	111T	7.0	6.5 - 8.0	3.4	50	1090 2403	248	9.8	750 29.5	9.8 12.3	337	2288	720	A A	-		
P245/75 R16	109T	7.0	6.5 - 8.0	3.5	51	1030 2271	248	9.8	774 30.5	9.8 12.3	347	2361	720	A A	-		

XL : Extra Load



CRUGEN HT51

Highway Terrain



English

- Long tread life with all season capabilities
- Excellent safety on the road covered with snow
- With 3D Sipe application, handling performance and snow traction performance have been improved
- M+S and 3PMSF (3 Peak-Mountain-Snowflake) certified



Español

- Capacitada con una larga vida de la banda de rodadura para todas las estaciones
- Excelente seguridad para camino cubierto de nieve
- Ranuras tridimensionales que mejoran el manejo y la tracción en la nieve
- Marcaje M+S y 3PMSF (3 Picos de Montaña y Copo de Nieve)



Português

- Longa vida do piso com todas as capacidades da época
- Excelente segurança na estrada coberta de neve
- Com a aplicação de ranhuras 3D, a dirigibilidade e o desempenho de tração em neve e lama foram melhorados
- Com marcação M+S e símbolo 3PMSF (3 floco de neve em topo de montanha)



Français

- Pneu toutes saisons avec une longévité de la bande de roulement prolongée
- Une excellente sécurité sur route enneigée
- Grâce à la lamellisation 3D, la tenue de route et la traction sur neige sont améliorées
- Marquage M+S et 3PMSF (3 Pics de Montagnes Symbole Flocon de neige)



Highway Terrain All Season Handling 3PMSF

Award & Test Results



Consumer Reports (2021.06)
: Ranking 5

Rim	Tire Size	Measuring Rim Width	Approved Rim Width	Max. Air Pressure		Max. Load		Section Width		Overall Diameter		Tread Depth	Static Loaded Radius	Rolling Circumference	UTQG	Rim Protector					
				bar	psi	kg	lbs	mm	inch	mm	inch						mm	x/32"			
Black Sidewall																					
16"	LT 245/75 R16 10	S 120S	7.0	6.5 - 8.0	5.5	80	1380	3042	248	9.8	774	30.5	11.2	14.1	347	2361	-	-	-	-	
																	D 116	1260	2778		
	235/60 R16 XL	104T	7.0	6.5 - 8.5	3.4	50	900	1985	240	9.4	688	27.1	9.8	12.3	313	2098	720	A	A	-	-
	235/65 R16C 10	S 121R	7.0	6.5 - 7.5	5.8	83	1450	3195	242	9.5	708	27.9	11.3	14.2	321	2159	-	-	-	-	-
	235/70 R16	106T	7.0	6.0 - 8.0	3.5	51	950	2094	240	9.4	736	29.0	9.8	12.3	332	2245	720	A	A	-	-
	LT 235/85 R16 10	S 120R	6.5	6.0 - 7.5	5.5	80	1380	3042	235	9.3	806	31.7	11.2	14.1	359	2458	-	-	-	-	-
	225/70 R16	103T	6.5	6.0 - 7.5	3.5	51	875	1929	228	9.0	722	28.4	9.8	12.3	326	2202	720	A	A	-	-
	LT 225/75 R16 10	S 115S	6.0	6.0 - 7.0	5.5	80	1215	2680	223	8.8	744	29.3	11.2	14.1	335	2269	-	-	-	-	-
225/75 R16C 10	S 121R	6.0	6.0 - 7.0	5.8	83	1450	3195	225	8.9	741	29.2	11.4	14.4	334	2260	-	-	-	-	-	
																					D 120
215/65 R16 XL	102T	6.5	6.0 - 7.5	3.4	50	850	1874	221	8.7	686	27.0	9.8	12.3	312	2092	720	A	A	-	-	
																					P215/70 R16
LT 215/85 R16 10	S 115R	6.0	5.5 - 7.0	5.5	80	1215	2680	216	8.5	772	30.4	11.2	14.1	346	2355	-	-	-	-	-	
																					D 112
215/85 R16C 10	S 115Q	6.0	5.5 - 7.0	5.8	83	1215	2680	225	8.9	768	30.2	11.3	14.2	344	2342	-	-	-	-	-	
																					D 112
15"	255/70 R15	108T	7.5	6.5 - 8.5	3.5	51	1000	2205	260	10.2	739	29.1	9.8	12.3	330	2254	720	A	A	-	-
	LT 235/75 R15 06	S 104S	6.5	6.0 - 7.0	3.4	50	900	1985	235	9.3	733	28.9	11.2	14.1	328	2236	-	-	-	-	-
	235/75 R15 XL	109T	6.5	6.0 - 8.0	3.4	50	1030	2271	235	9.3	733	28.9	9.8	12.3	328	2236	720	A	A	-	-
	215/70 R15	98T	6.5	5.5 - 7.0	3.5	51	750	1653	221	8.7	683	26.9	9.8	12.3	308	2083	720	A	A	-	-
		D 92																			

XL : Extra Load